

TYPE NO.: AOM880GF5A

- Full omni-directional radiation pattern
- DC-grounded (DC-short) - antistatic
- NO GROUNDPLANE NEEDED


ELECTRICAL SPECIFICATIONS:

FREQUENCY	824 - 894 MHz (GSM850, ISM a.o.)
IMPEDANCE	50 ohm
POLARISATION	Vertical
GAIN	5 dBd, 7.1 dBi
BANDWIDTH	70 MHz
VSWR	< 1.5
MAX. POWER	200 W

MECHANICAL SPECIFICATIONS:

COLOR	White
HEIGHT	Approx. 1440 mm
WEIGHT	550 g
MOUNTING	On 1" threaded pole (G1"-11 thread) with Revolving Nut Kit or on optionally brackets
MATERIALS	PU-painted heavy-duty Ø 18 mm glass-fibre tube and chrome plated brass
OPERATING TEMPERATURE	-40C to +70C
CONNECTOR 1	N-female
CABLE	No cable supplied
MOUNTING PLACE	On deck or mast etc.
INGRESS PROTECTION	IP66
ORDER NO.	AOM880GF5A

VERTICAL RADIATION PATTERN:



IKM Communication ApS
 Lyngvej 16, Building C
 Noerre Herlev
 DK3400 Hilleroed
 Denmark

Phone DK +45 2990 0919
 Phone SE +46 4104 3460
 e-mail sales@ikmcom.dk
 Website www.ikmcom.dk

CVR/VAT No. DK 36 05 76 88
 IBAN DK5030000011482724
 SWIFT DABADKK